



Cable heads are used to create a mechanical and electrical connection between the wire line and tool string. The cable head is also intended to be the “weak link” if the tool string becomes stuck within the wellbore. The wireline will pull out of the cable head when the predetermined force is applied.

Temperature rating:	500°F
Pressure rating:	20,000 psi
Tool diameter range:	3/4" - 1 11/16" O.D.
Tool length:	Varies
Type:	“GO” Brass Cone and Washer & Knock Down (Clamp Ring Style)
Fishneck:	1" & 1 3/8" O.D.
Connections:	“GO” Gearheart



# CABLE HEADS



1 1/16" FISHNECK w/ 1 3/8" O.D. NECK  
1 7/16" FISHNECK w/ 1" O.D. NECK



1" CLAMP RING & ROPE SOCKET  
1 3/8" BRASS CONE & WASHER



CABLEHEAD ACCESSORIES

Item Number	Item Description
<b>3/4" O.D. CABLEHEADS</b>	
CHD2001-(LINE SIZE)	CABLEHEAD "KNOCK DOWN", 3/4" X (LINE SIZE)
<b>1" O.D. CABLEHEADS</b>	
CHD3001-(LINE SIZE)	CABLEHEAD "KNOCK DOWN", 1" X (LINE SIZE)
<b>1 3/8" O.D. CABLEHEADS</b>	
CHD4001-(LINE SIZE)	CABLEHEAD "GO", 1 3/8" X (LINE SIZE)
<b>1 7/16" O.D. CABLEHEADS</b>	
CHD5001-(LINE SIZE)	CABLEHEAD "GO", 1 7/16" X (LINE SIZE)
CHD5002-(LINE SIZE)	CABLEHEAD "KNOCK DOWN", 1 7/16" X (LINE SIZE)
CHD5003-(LINE SIZE)	CABLEHEAD "GO", 1 7/16" X (LINE SIZE) 1 3/8" FISHNECK
<b>1 11/16" O.D. CABLEHEADS</b>	
CHD6001-(LINE SIZE)	CABLEHEAD "GO", 1 11/16" X (LINE SIZE)
CHD6002-(LINE SIZE)	CABLEHEAD "KNOCK DOWN", 1 11/16" X (LINE SIZE)
<b>COMPONENTS</b>	
CHD-075002-(LINE SIZE)	CLAMP RING, 3/4"
CHD-075003-(LINE SIZE)	ROPE SOCKET, 3/4"
CHD-100001-(LINE SIZE)	CLAMP RING, 1"
CHD-100002-(LINE SIZE)	ROPE SOCKET, 1"
CHD-143010-(LINE SIZE)	BRASS CONE
CHD-143013	BRASS WAHSER
CHD-143013S	BRASS SHIM WAHSER
CHD-143006-(LINE SIZE)	FISHNECK, 1 7/16"

