



De-centralizers are used within the tool string to keep the tools de-centralized within the casing. They can also be used for phasing when companies are perforating. Advanced De-Centralizers are manufactured with either channel or button type magnets.

Temperature rating:	500°F
Pressure rating:	20,000 psi
Tool diameter range:	1 3/8" - 2" O.D.
Tool length:	Varies
Types:	Channel or Button Magnets
Connections:	"GO" Gearheart or RTG (Bolt Together)



DE-CENTRALIZERS

ADVANCED E-LINE SOLUTIONS



**BUTTON MAGNETS
CHANNEL MAGNETS**

ITEM #	DESCRIPTION	O.D.
DEC4001	DECENTRALIZER "GO", 1 3/8" (CHANNEL)	1 3/8"
DEC6001	DECENTRALIZER "GO", 1 11/16" (CHANNEL)	1 11/16"
DEC6002	DECENTRALIZER RTG, 1 9/16" (CHANNEL)	1 9/16"
DEC6003	DECENTRALIZER RTG, 1 11/16" (CHANNEL)	1 11/16"
DEC6004	DECENTRALIZER "GO", 1 9/16" (CHANNEL)	1 9/16"
DEC6005	DECENTRALIZER "GO", 1 11/16" (BUTTON)	1 11/16"
DEC9001	DECENTRALIZER "GO", 2 1/8" (BUTTON)	2 1/8"
DEC9002	DECENTRALIZER RTG, 2" (CHANNEL)	2"
DEC9003	DECENTRALIZER "GO", 2" (BUTTON)	2"
DEC9004	DECENTRALIZER RTG, 2" (BUTTON)	2"



**"GO" CONNECTION
RTG CONNECTION**



222 BURGESS DRIVE UNIT #4 , BROUSSARD, LA. 70518 email: sales@ae-ls.com office: 337-330-2634

Visit us at: www.ae-ls.com